

# SPD2025-12X

## GaAs PIN Photodiode 1x12 Array



### FEATURES

- Large aperture
- 20 GHz bandwidth
- Low capacitance

### APPLICATIONS

- 12x25Gb/s links
- 300G HPC Mid-Board Optics
- Multimode datacom

Cosemi's SPD2025-12X is a mesa-structured, GaAs-based 1x12 PIN photodiode array offering high responsivity, low dark current and low capacitance for high bandwidth, high performance optical receiver designs. The photodiodes' low parasitics make it ideal for high speed, multimode 12x25Gb/s and 12x28Gb/s applications. The SPD2025 is also available in singlets (SPD2025) and 1x4 array sizes (SPD2025-4X).

Copyright © 2016 Cosemi Technologies, Inc. All Rights Reserved.

Information contained in this document is proprietary and confidential to Cosemi. This document may not be reproduced, distributed or disclosed to any third-party without the express written consent of Cosemi. Product processing does not necessarily include testing of all parameters. Cosemi reserves the right to change the configuration and performance of the products or to discontinue products at any time.

### Cosemi Technologies, Inc.

1370 Reynolds Ave., Suite 100  
Irvine, CA 92614  
Tel. 949.623.9816 | Fax. 949.623.9817  
Email: [info@cosemi.com](mailto:info@cosemi.com)  
Website: [www.cosemi.com](http://www.cosemi.com)